

# PRODUCT DATA SHEET

## INSULATED CORD END TERMINALS FRENCH NORM



### DESCRIPTION

Cable End Terminals are designed to terminate the end of a cable. Cable, screw type terminal blocks or the crimped terminal at the cable end protects the exposed ones before installing the connectors.

### FEATURES

- Standard : DIN 46228
- Material : Copper, Tin Plated
- Insulation : Nylon
- Operating Temperature : Maximum From 105° to 600 Volts

### MARKINGS



















- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.

# PRODUCT DATA SHEET

## INSULATED CORD END TERMINALS FRENCH NORM

### SECTIONS AND DIMENSIONS



PRODUCT CODE	COLOUR	CABLE SECTION (mm <sup>2</sup> )	DIMENSIONS (mm)				
			F	L	W	B	D
IYF - 0.25	 Violet	0.25 mm <sup>2</sup>	8.0	12.0	1.9	4.4	1.1
IYF - 0.34	 Pink	0.34 mm <sup>2</sup>	8.0	12.0	1.9	4.4	1.1
IYF - 0.50	 White	0.50 mm <sup>2</sup>	8.0	14.0	2.6	6.0	1.3
IYF - 0.75	 Blue	0.75 mm <sup>2</sup>	8.0	14.0	2.8	6.3	1.5
IYF - 1.0	 Red	1.00 mm <sup>2</sup>	8.0	14.0	3.0	6.3	1.7
IYF - 1.5	 Black	1.50 mm <sup>2</sup>	8.0	14.0	3.5	6.3	2.0
IYF - 2.5	 Grey	2.50 mm <sup>2</sup>	8.0	14.0	4.2	7.4	2.5
IYF - 4.0	 Orange	4.00 mm <sup>2</sup>	10.0	17.0	4.8	7.4	3.2
IYF - 6.0	 Green	6.00 mm <sup>2</sup>	12.0	20.0	6.3	8.5	3.9
IYF - 10.0	 Brown	10.0 mm <sup>2</sup>	12.0	22.0	7.6	8.8	4.9
IYF - 16.0	 Beige	16.0 mm <sup>2</sup>	12.0	24.0	8.8	10.0	6.2
IYF - 25.0	 Black	25.0 mm <sup>2</sup>	16.0	28.0	11.2	12.0	7.7
IYF - 35.0	 Red	35.0 mm <sup>2</sup>	16.0	30.0	12.7	14.0	8.7
IYF - 50.0	 Blue	50.0 mm <sup>2</sup>	20.0	36.0	15.0	16.0	10.9
IYF - 70.0	 Yellow	70.0 mm <sup>2</sup>	21.0	37.0	16.0	17.0	14.3