

PRODUCT DATA SHEET NON-INSULATED CORD END TERMINALS



DESCRIPTION

It provides ease of installing wire on the terminal block. It meets DIN standards for wire enclosure. Suitable for limited space panel applications. Multiple pin lengths are available for various terminal blocks.

FEATURES

- Standard : DIN 46228
- Material : Copper, Tin Plated
- Insulation : None


MARKINGS



- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.







٠D

SECTIONS AND DIMENSIONS

PRODUCT CODE	CABLE SECTION (mm²)	DIMENSIONS (mm)			
		L	W	D	С
KY – 0.50	0.50 mm ²	10	2.1	1.3	1.0
KY – 0.75	0.75 mm ²	10	2.3	1.5	1.2
KY – 1.0	1.00 mm ²	10	2.5	1.7	1.4
KY – 1.5	1.50 mm ²	10	2.8	2.0	1.7
KY – 2.5	2.50 mm ²	12	3.4	2.5	2.2
KY - 4.0	4.00 mm ²	12	4.0	3.2	2.8
KY - 6.0	6.00 mm ²	12	4.7	3.9	3.5
KY – 10.0	10.0 mm ²	15	5.8	4.9	4.5
KY – 16.0	16.0 mm ²	15	7.5	6.2	5.8
KY – 25.0	25.0 mm ²	16	9.1	7.9	7.5
KY - 35.0	35.0 mm ²	16	10.2	8.7	8.3
KY - 50.0	50.0 mm ²	22	12.7	10.9	10.3