

PRODUCT DATA SHEET

INSULATED RING TERMINALS



DESCRIPTION

Insulated Ring Terminals connect an electrical cable, wire to a stud, or to an electrical component such as a battery terminal. It is used to tie it to a pole.

FEATURES

- | | |
|-------------------------|----------------------------------|
| - Standard | : DIN 46237 |
| - Material | : Copper, Tin Plated |
| - Insulation | : PVC |
| - Operating Temperature | : Maximum From 105° to 600 Volts |

MARKINGS




- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.

PRODUCT DATA SHEET

INSULATED RING TERMINALS

SECTIONS AND DIMENSIONS



PRODUCT CODE	COLOUR	CABLE SECTION (mm ²)	BOLT SIZE	DIMENSIONS (mm)					
				d2	d3	l	d1	d4	a
GYU - 301	Red	0.50 - 1.50 mm ²	M3	3.2	6.0	16.0	1.6	4.0	10.0
GYU - 401	Red		M4	4.3	8.0	17.0	1.6	4.0	10.0
GYU - 501	Red		M5	5.3	10.0	18.0	1.6	4.0	10.0
GYU - 601	Red		M6	6.5	10.0	18.0	1.6	4.0	10.0
GYU - 801	Red		M8	8.4	14.0	22.0	1.6	4.0	10.0
GYU - 302	Blue	1.50 - 2.50 mm ²	M3	3.2	6.0	16.0	2.3	4.5	10.0
GYU - 402	Blue		M4	4.3	8.0	17.0	2.3	4.5	10.0
GYU - 502	Blue		M5	5.3	10.0	19.0	2.3	4.5	10.0
GYU - 602	Blue		M6	6.5	11.0	20.0	2.3	4.5	10.0
GYU - 802	Blue		M8	8.4	14.0	22.0	2.3	4.5	10.0
GYU - 1002	Blue		M10	10.5	15.0	22.0	2.3	4.5	10.0
GYU - 406	Yellow	4.00 - 6.00 mm ²	M4	4.3	8.6	21.0	3.6	6.3	13.0
GYU - 506	Yellow		M5	5.3	10.0	22.0	3.6	6.3	13.0
GYU - 606	Yellow		M6	6.5	11.0	22.5	3.6	6.3	13.0
GYU - 806	Yellow		M8	8.4	14.0	26.0	3.6	6.3	13.0
GYU - 1006	Yellow		M10	10.5	18.0	28.0	3.6	6.3	13.0
GYU - 1206	Yellow		M12	13.0	18.0	28.0	3.6	6.3	13.0
GYU - 610	Red	8.00 - 10.00 mm ²	M6	6.7	23.5	30.0	4.5	8.0	17.0
GYU - 810	Red		M8	8.4	26.3	36.0	4.5	8.0	17.0