

# PRODUCT DATA SHEET

## INSULATED BULLET MALE DISCONNECTS



### DESCRIPTION

Insulated Bullet Male Disconnects separate high quality insulated terminals.

### FEATURES

- |                         |                                      |
|-------------------------|--------------------------------------|
| - Standard              | : DIN 46237                          |
| - Material              | : Brass, Tin Plating, Copper Ferrule |
| - Insulation            | : PVC                                |
| - Operating Temperature | : Maximum From 75° to 600 Volts      |

### MARKINGS




- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.

# PRODUCT DATA SHEET

## INSULATED BULLET MALE DISCONNECTS

### SECTIONS AND DIMENSIONS



PRODUCT CODE	COLOUR	CABLE SECTION (mm <sup>2</sup> )	DIMENSIONS (mm)				
			W	F	L	B	D
GBE - 1040	Red	0.50 - 1.50 mm <sup>2</sup>	4.0	8.5	21.5	10.5	3.8
GBE - 2050	Blue	1.50 - 2.50 mm <sup>2</sup>	5.0	8.5	21.2	10.5	4.7
GBE - 5050	Yellow	4.00 - 6.00 mm <sup>2</sup>	5.0	8.5	24.0	13.0	6.2