

PRODUCT DATA SHEET

INSULATED FEMALE DISCONNECTS



DESCRIPTION

Insulated Female Disconnects, increased safety and reliability of electrical connectors designed to meet the demands.

FEATURES

- Standard : DIN 46237
- Material : Brass, Tin Plating
- Insulation : PVC
- Operating Temperature : Maximum From 75° to 600 Volts

MARKINGS




- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.

PRODUCT DATA SHEET

INSULATED FEMALE DISCONNECTS

SECTIONS AND DIMENSIONS



PRODUCT CODE	COLOUR	CABLE SECTION (mm ²)	SOCKET WIDTH	DIMENSIONS (mm)				
				W	F	L	B	D
GFD - 1288	Red	0.50 - 1.50 mm ²	0.8 x 2.80	3.2	6.5	19.0	10.5	3.8
GFD - 1488	Red		0.8 x 4.75	5.0	6.4	19.4	10.5	3.8
GFD - 1638	Red		0.8 x 6.35	6.6	7.5	20.8	10.5	3.8
GFD - 2288	Blue	1.50 - 2.50 mm ²	0.8 x 2.80	3.2	6.5	19.0	10.5	4.7
GFD - 2488	Blue		0.8 x 4.75	5.0	6.4	19.4	10.5	4.7
GFD - 2638	Blue		0.8 x 6.35	6.6	7.5	20.8	10.5	4.7
GFD - 5638	Yellow	4.00 - 6.00 mm ²	0.8 x 6.35	6.6	7.5	23.3	13.0	6.2