

PRODUCT DATA SHEET

FULLY INSULATED POLYAMIDE FEMALE DISCONNECTS



DESCRIPTION

Fully Insulated Polyamide Female Disconnects are designed to offer improved mechanical and electrical integrity under heavy-duty cable termination applications using ring terminals.

FEATURES

- | | |
|-------------------------|----------------------------------|
| - Standard | : DIN 46237 |
| - Material | : Brass, Tin Plating |
| - Insulation | : Polyamide |
| - Operating Temperature | : Maximum From 105° to 600 Volts |

MARKINGS




- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.

PRODUCT DATA SHEET

FULLY INSULATED POLYAMIDE FEMALE DISCONNECTS

SECTIONS AND DIMENSIONS



PRODUCT CODE	COLOUR	CABLE SECTION (mm ²)	SOCKET WIDTH	DIMENSIONS (mm)				
				W	F	L	B	D
GPFD - 1638	Red	0.50 - 1.50 mm ²	0.8 x 6.35	6.6	7.5	21.5	11.0	4.0
GPFD - 2638	Blue	1.50 - 2.50 mm ²	0.8 x 6.35	6.6	7.5	21.5	11.0	5.0
GPFD - 5638	Yellow	4.00 - 6.00 mm ²	0.8 x 6.35	6.6	7.5	24.2	13.0	6.5