

PRODUCT DATA SHEET

INSULATED MALE DISCONNECTS



DESCRIPTION

Insulated Male Disconnects, internal barrel notches grip cables tightly to resist pulling and reduce electrical resistance.

FEATURES

- Standard : DIN 46237
- Material : Brass, Tin Plating
- Insulation : PVC
- Operating Temperature : Maximum From 75° to 600 Volts

MARKINGS




- It complies with RoHS standards.
- It complies with UKAS Quality Management standards.
- It complies with CE standards.
- It complies with UL standards.

PRODUCT DATA SHEET

INSULATED MALE DISCONNECTS

SECTIONS AND DIMENSIONS



PRODUCT CODE	COLOUR	CABLE SECTION (mm ²)	SOCKET WIDTH	DIMENSIONS (mm)				
				W	F	L	B	D
GFE - 1288	Red	0.50 - 1.50 mm ²	0.8 x 2.80	2.8	6.5	19.2	10.5	3.8
GFE - 1488	Red		0.8 x 4.75	4.8	6.7	19.8	10.5	3.8
GFE - 1638	Red		0.8 x 6.35	6.35	6.35	21.8	10.5	3.8
GFE - 2288	Blue	1.50 - 2.50 mm ²	0.8 x 2.80	2.8	6.7	19.8	10.5	4.7
GFE - 2488	Blue		0.8 x 4.75	4.8	6.7	19.8	10.5	4.7
GFE - 2638	Blue		0.8 x 6.35	6.35	7.7	21.8	10.5	4.7
GFE - 5638	Yellow	4.00 - 6.00 mm ²	0.8 x 6.35	6.35	7.7	24.8	13.0	6.2